



Suggested Fasteners

for Installing Nominal 1" or 5/4" TechTrim

NOTE: Longer fasteners than specified must be used as needed to ensure the pointed end of the fastener penetrates structural material (e.g., dimensional lumber) by at least one inch.

FOR HAND NAILED APPLICATIONS

| TYPE | SIZE | LENGTH | SHANK DIAMETER | HEAD DIAMETER | MATERIAL | DESCRIPTION |
|---------------|-------------------------|-----------|------------------------|--------------------|---------------------------------------|--------------|
| | number in "d" = pennies | in inches | in inches and/or gauge | in inches or gauge | | |
| Finishing | 8d | 2-1/2" | 0.095" 12.5 ga | 9.5 ga | Hot-dip galvanized or stainless steel | Smooth shank |
| Common or box | 8d | 2-1/2" | 0.131" 10.25 ga | 9/32" | Hot-dip galvanized or stainless steel | Smooth shank |

FOR PNEUMATIC GUN APPLICATIONS*

| PRODUCT CODE | LENGTH | SHANK DIAMETER | HEAD DIAMETER | MATERIAL | DESCRIPTION |
|---|-----------|----------------|---------------|---------------------|--------------|
| | in inches | in inches | in inches | | |
| HITACHI FASTENERS for NV65AH or NV75AG SIDING NAILER (plastic sheet collated round head nails) | | | | | |
| #13325 or #13385 | 2-1/4" | 0.092" | 13/64" | Hot-dip galvanized | Ring shank |
| #13328 or #13388 | 2-1/4" | 0.092" | 13/64" | Hot-dip galvanized | Smooth shank |
| #13330 or #13390 | 2-1/2" | 0.092" | 13/64" | Hot-dip galvanized | Ring shank |
| #13331 or #13389 | 2-1/2" | 0.092" | 13/64" | Hot-dip galvanized | Smooth shank |
| #13391 | 3" | 0.131" | 7/32" | Hot-dip galvanized | Smooth shank |
| #13327 or #13387 | 2-1/4" | 0.092" | 13/64" | 304 stainless steel | Ring shank |
| #13386 | 2-1/4" | 0.092" | 13/64" | 304 stainless steel | Smooth shank |
| MAZE NAILS 15 DEGREE PLASTIC COIL-ATED NAILS (Available painted. Visit www.mazenails.com) | | | | | |
| CLCEM116A | 2-1/4" | 0.095" | 0.235" | Hot-dip galvanized | Ring shank |
| CLCEM117A | 2-1/2" | 0.095" | 0.235" | Hot-dip galvanized | Ring shank |
| CLCEM119A | 3" | 0.095" | 0.235" | Hot-dip galvanized | Ring shank |
| CLCEM116 | 2-1/4" | 0.095" | 0.235" | Hot-dip galvanized | Smooth shank |
| CLCEM117 | 2-1/2" | 0.095" | 0.235" | Hot-dip galvanized | Smooth shank |
| CLCEM119 | 3" | 0.095" | 0.235" | Hot-dip galvanized | Smooth shank |
| CLSSCEM117A | 2-1/2" | 0.099" | 0.235" | 304 stainless steel | Ring shank |
| CLSSPVC8 | 2-1/2" | 0.099" | 0.219" | 304 stainless steel | Smooth shank |
| CLSSPVC10 | 3" | 0.099" | 0.219" | 304 stainless steel | Smooth shank |

* Other brand name fasteners can be used if they equal or exceed the minimum shank diameter (0.092"), material, and description specifications.